



# DURACURE B

## DESCRIPTION

Duracure B is a PVA based, pink coloured economical liquid membrane curing compound for freshly poured concrete, which dries clear. It enables the curing of the concrete by reducing loss of water from the concrete.

## USES

- Suitable for internal and external use on freshly poured concrete in applications such as concrete paving and floors, paths, driveways, car parks, etc.
- It may be used to help retard evaporation of the mix water and assist in achieving better hydration of the cement.

## FEATURES AND BENEFITS

- Will not impair the bond of most surface finishes such as paint, carpet adhesives, renders or sand/cement toppings.
- Assists in achieving better hydration of the cement resulting in greater compressive strength.
- Does not yellow, allowing application both outside and inside.
- Dyed pink to enable you to easily identify coated areas.
- Reduces surface shrinkage and cracking.

## APPLICATION

- Apply by low pressure spray or long nap roller following the final finishing operation of the concrete, when the surface has hardened sufficiently to prevent marking. Care must be taken to ensure a continuous uniform film.

## PRECAUTIONS

- Do not allow the product to freeze.
- Do not use in temperatures above 45°C and below 5°C.
- Do not use in situations where the Duracure will remain permanently moist, eg. where overcoated with an impervious floor covering, or in a wet service area.

## COVERAGE

Steel trowelled finish: 8 - 10M<sup>2</sup>/Litre  
Wood float finish: 5 - 7m<sup>2</sup>/Litre

## CLEAN UP

Rollers and spray equipment may be cleaned in fresh water while product is still wet.

## PACKAGING

20 litre pails.  
200 litre drums.

## SHELF LIFE

Approximately 12 months in unopened containers, stored in a dry cool place.

## TECHNICAL DATA

<b>Properties:</b>	
<b>Appearance:</b>	Pink Coloured Liquid
<b>Flash Point:</b>	Non-Flammable
<b>Thinning:</b>	Not Necessary
<b>Solubility In Water:</b>	Dispersable

## DISCLAIMER

*The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. All workmanship must be carried out in accordance with AS 3740 - 1994.*

*The information contained herein is to the best of our knowledge true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for a particular application. Users are asked to check that the literature in their possession is the latest issue.*

# Davco

**Davco Construction Materials Pty Limited**

ABN 28 093 876 558

67 Elizabeth Street Wetherill Park NSW Australia 2164

Telephone: 61 2 9616 3000 Facsimile: 61 2 9725 5551

Toll Free Technical Advisory Line: 1800 653 347

Offices: Sydney, Melbourne, Brisbane, Perth, Singapore & Thailand

Email: [marketing@davco.com.au](mailto:marketing@davco.com.au) Website: [www.davco.com.au](http://www.davco.com.au)

PAREXGROUP