



FLASHCRETE

QUICKSET SAND CEMENT MIX

DESCRIPTION

Flashcrete is a 15 minutes quickset sand cement mix. It contains a mixture of selected sand, Portland cement plus additives which will produce a quickset sand cement mix.

USES

- Suitable for setting of vitreous sanitary ware.
- Suitable for repairs to sand/cement renders, small holes in pedestrian footpaths etc.

FEATURES AND BENEFITS

- Ready to use – just add water
- Hard set in 15 minutes.

APPLICATION

- Be aware of stiffening time – 15 minutes.
- Do not use mechanical mixer.
- The priming of surfaces with water or the use of an acrylic or SBR bonding agent is essential for good adhesion.
- Empty contents of pail or portion required of Flashcrete into wheelbarrow or onto a smooth hard surface, protected from wind.
- Gradually add approximately 1-1.5 litres of clean water per 8kg of Flashcrete (15-20% water by weight), mixing thoroughly to obtain a workable mix.
- Place Flashcrete in position immediately and finish the joint promptly.
- Moist cure when practicable – wet down the joint periodically for a period of 7 days to aid curing.
- Flashcrete is subject to ambience weather conditions. In extreme temperatures of summer use cool water when mixing and alternatively in winter warm water may be necessary.

COVERAGE

As a rough guide, a 8kg pail of Flashcrete will provide sufficient mortar to bed a toilet pan. A 8kg pail will cover approximately 0.5m² at 10mm thick.

PRECAUTIONS

- Adequate precaution should be taken to avoid direct bodily contact with the contents of the pack

or the fresh concrete prepared from them, as cement powder and/or freshly mixed concrete may cause irritation to the eyes, nose, throat and/or skin including alkaline burning and dermatitis.

- If direct contact occurs, wash the affected part immediately and repeatedly with clean fresh water. If any irritation persists, seek medical attention without delay.

CLEAN-UP

Thoroughly clean all equipment with water.

PACKAGING

Flashcrete is packed in 8kg pails.

SHELF LIFE AND STORAGE

Store under cover, above the ground level and away from direct heat and moisture.

DISCLAIMER

The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage.

The information contained herein is to the best of our knowledge true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for a particular application. Users are asked to check that the literature in their possession is the latest issue.

PAREXDAVCO

ParexDavco (Australia) Pty Limited

ABN 28 093 876 558

67 Elizabeth Street Wetherill Park NSW 2164 Australia

Telephone: 61 2 9616 3000 Facsimile: 61 2 9725 5551

Toll Free Technical Advice Line: 1800 653 347

Email: technical@parexdavco.com.au Website: www.parexdavco.com.au

