



# **SANITIZED<sup>®</sup> SUPERFINE WHITE GROUT**

---

## **DESCRIPTION**

---

*Sanitized<sup>®</sup>* Superfine White Grout is a cementitious grout designed for use with most types of ceramic tiles and natural stone applications. The grout also contains a biocide, which provides it with a resistance to a broad spectrum of moulds and bacteria.

## **USES**

---

- *Sanitized<sup>®</sup>* Superfine White Grout can be used in wall grout joints that are between 1 - 3mm wide.
- *Sanitized<sup>®</sup>* Superfine White Grout is only suitable for internal wall grouting applications.

## **SURFACE PREPARATION**

---

- Before commencing grouting, ensure the tile adhesive has set firmly. This usually requires 24 hours with the majority of tile adhesives.
- Remove any spacer lugs, rake-out any excess adhesive and any loose or foreign material from the grout joints.
- In general, ensure the grout joints are clean and dry.

## **MIXING**

---

- Add clean water to a bucket, then slowly add the *Sanitized<sup>®</sup>* Superfine White Grout powder to the water. Stir the mix until a lump-free consistency is achieved.
- The mixing ratio is 20kg powder to 5.5 - 6lt of water.
- Allow the mix to stand for 10 minutes, re-stir, then use the grout.
- Where movement is expected, or for superior performance in general applications, use Davco 4 in 1 Grout Additive instead of water.

## **APPLICATION**

---

- Prior to grouting it is advisable to lightly dampen the grout joints, particularly with porous tiles or in hot conditions.

- Using a rubber float or squeegee, work the grout into the joints in a diagonal motion making sure that the grout does not just sit on top of the joint i.e. the grout does not bridge the joint.
- Remove excess grout from the surface of the tiles with the rubber float or squeegee using a diagonal motion.
- Use a damp sponge to clean up the remainder of the grout. Regularly rinsing the sponge out to assist in cleaning.
- Allow the grout to cure for 24 hours before cleaning the grout haze with a soft dry cloth. Hard to remove haze can be cleaned with Davco *Sanitized<sup>®</sup>* Tile & Grout Cleaner.

## **PRECAUTIONS**

---

- Do not apply *Sanitized<sup>®</sup>* Superfine White Grout in temperatures above 40°C or below 5°C.
- *Sanitized<sup>®</sup>* Superfine White Grout is not suitable for use in harsh and demanding environments or where there are hygienic requirements i.e. commercial kitchens, public toilets, food processing plants etc. Use Davco Grout-Cure for these types of installations. Refer to the Grout-Cure datasheet for full instructions.
- Cleaning or discolouration problems can occur with either textured, porous or natural stone tiles.
- Do not use *Sanitized<sup>®</sup>* Superfine White Grout on floors or in immersed situations i.e. swimming pools, spas etc.
- Do not apply *Sanitized<sup>®</sup>* Superfine White Grout in movement joints, use Davco *Sanitized<sup>®</sup>* Colorcaulk or Davsil.
- Do not apply neat or strong acids on *Sanitized<sup>®</sup>* Superfine White Grout.
- For other uses or the use of *Sanitized<sup>®</sup>* Superfine White Grout in situations not mentioned in these instructions, contact your ParexDavco (Australia) Pty Ltd state office.
- Being cement based, *Sanitized<sup>®</sup>* Superfine White Grout is alkali in nature, which can cause dermatitis. Thus when using *Sanitized<sup>®</sup>* Superfine White Grout it is recommended that applicators should wear PVC or similar gloves and safety goggles.



# SANITIZED<sup>®</sup> SUPERFINE WHITE GROUT

- For a full MSDS on this product, contact your ParexDavco (Australia) Pty Ltd state office.
- All products are guaranteed when installed in accordance with the relevant Australian Standard, the current technical datasheets, specification and instructions for use. This guarantee does not cover issues beyond the control of the manufacturer such as efflorescence, shade variations, variable application techniques and extreme environmental conditions.

## CLEAN UP

Tools and other equipment can be cleaned up with water while grout is still wet.

## PACKAGING

*Sanitized*<sup>®</sup> Superfine White Grout is available in 1kg, 2kg, 5kg, 10kg and 20kg bags.

## COVERAGE

The coverage of the grout will vary depending upon the texture, size and thickness of the tile and the width of the grout joint.

Use the table below as a general guide:

Tile Size (mm)	Qty of Grout Required kg/m <sup>2</sup> Joint Width (mm)		
	1.5	3	5
50 x 50 x 6	0.8	1.6	--
150 x 150 x 6	0.3	0.6	--
200 x 100 x 6	0.3	0.6	--
200 x 200 x 6	0.2	0.4	--

## SHELF LIFE

*Sanitized*<sup>®</sup> Superfine White Grout has a shelf life of up to 12 months in unopened bags stored in a cool, dry elevated place.

## TECHNICAL DATA

Properties:	
Appearance:	White Powder
Bulk Density:	~ 1.3 kg/litre
Pot Life at 20°C:	40 minutes
Curing Time at 20°C:	24 hours

## DISCLAIMER

*The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. All workmanship must be carried out in accordance with AS 3958.1 - 1991.*

*The information contained herein is to the best of our knowledge true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for a particular application. Users are asked to check that the literature in their possession is the latest issue.*

# PAREX DAVCO

ParexDavco (Australia) Pty Limited

ABN 28 093 876 558

67 Elizabeth Street Wetherill Park NSW 2164 Australia

Telephone: 61 2 9616 3000 Facsimile: 61 2 9725 5551

Toll Free Technical Advice Line: 1800 653 347

Email: [technical@parexdavco.com.au](mailto:technical@parexdavco.com.au) Website: [www.parexdavco.com.au](http://www.parexdavco.com.au)

